



LANDMASTER L7 CREW (4x4)



Shown with optional accessories.

HOOD COLORS	
FACTORY-INSTALLED PACKAGES	Untamed Trail Cruiser
BED OPTIONS	Poly Bed, Large Steel Bed, Flip Seat / Steel Bed
ENGINE	627EFI VANGUARD Commercial-Grade Engine
SPEED	35+ mph
ELECTRONIC POWER STEERING	Included
HAUL	600 lbs / 800 lbs (With HD Shocks)
TOW	1,500 lbs



AMERICAN MADE UTVs

L7 CREW (4x4)



THE BEST COMBINATION OF DURATION AND COVERAGE IN THE INDUSTRY

We build UTVs at American LandMaster with the intention of our customers never needing to use a warranty, but we know things can happen. The **Easy Life Warranty** from American LandMaster is a 12-month bumper-to-bumper limited warranty. Does limited sound confusing? It isn't. **As long as you care for your machine like you should, don't wreck it, or crush it, we're going to cover it.** Except for tires, brake pads, batteries, damage, neglect. That's the limit. Visit Landmaster.com to learn more.

POWER	23hp I 627cc Commercial-Grade, V-Twin OHV-Technology, EFI Vanguard 4-stroke Gas Engine. Superior balance, low vibration, lower emissions, improved valve life, better fuel economy and higher HP/Weight
SEATING CAPACITY	4 Person*
SPEED	35+ mph
FUEL CONSUMPTION	18 mpg*
RANGE	Up to 100 miles*
STARTING	12V keyed ignition
BATTERY	12V / 315 cca utility class
SPARK PLUG	NGK C7HSA
FUEL CAPACITY	5.0 gal
ALTERNATOR	16 amp
TRANSMISSION	CVT automatic
TRANSAXLE	Gear drive Schafer/DANA oil-filled transaxle
DIFFERENTIAL	Cable Actuated Rear-Locking
DRIVE	Switch engaged on demand, 4 wheel drive
FRONT SUSPENSION	Double A-arms, adjustable coil over shock with up to 8" travel
REAR SUSPENSION	Independent trailing arm, with radius rod, adjustable camber & tow control, dual-rate coil over shock with up to 8" of travel
BRAKE SYSTEM	4 wheel disc, hydraulic brake
TIRES	25 x 8 - 12 (front) 25 x 10 - 12 (rear)
DIMENSIONS	127" L x 58" W x 76" H (with poly bed)**
WHEEL BASE	105"
TURNING RADIUS	14' inside radius
GVWR	GVWR L-ROSS - 2,900 lbs. / HD L-ROSS - 3,100 lbs.
CURB WEIGHT	1,550 lbs.
BED MATERIALS	Structural foam "Poly Bed" with stake pockets
BED DIMENSIONS	35.25" L x 41.5" W x 11" D
BED CAPACITY	Poly - 9 cu.ft. / Steel - 11 cu.ft. / L-ROSS - 500 lbs. / HD L-ROSS - 700 lbs.
TOWING CAPACITY	1,500 lbs.
TOTAL PAYLOAD	L-ROSS - 1,400 lbs. / HD L-ROSS - 1,600 lbs.
WARRANTY	3 year engine / All other 1 year limited
ADDITIONAL FEATURES	3pt lap/shoulder belts for driver and passenger, twin 12V auxiliary outlets for accessories, 12V/18W LED headlights, polyurethane powder paint, 2" front and rear receiver hitch, poly dump bed standard, bench seating, welded steel frame. Complete weather-sealed wiring connections. Wide selection of additional accessories available along with three bed options. Fuel gauge located under seat. In-dash, hour/volt meter standard. EPS Standard

* Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances.

**Overall vehicle dimensions may vary with the addition of optional accessories