SPECIFICATIONS

POWER	9.5HP 277cc LandMAXX Commercial Power Engine by Kohler 4-Stroke OHV single cylinder with low oil shutdown	SPEED	Up to 22 mph**
FUEL CONSUMPTION	Up to 32 mpg**	RANGE	Up to 100 miles**
STARTING	12V keyed ignition with recoil backup	BATTERY	12V / 360 cca utility class
SPARK PLUG	NGK BKR5E	FUEL CAPACITY	5.0 gal
ALTERNATOR	10 amp	TRANSMISSION	CVT automatic
TRANSAXLE	Gear drive Schafer/DANA oil-filled transaxle	DIFFERENTIAL	Limited Slip Differential
DRIVE	2 wheel drive	FRONT SUSPENSION	Double A-arms, adjustable shocks with up to 3" travel
REAR SUSPENSION	Articulated rear swing arm, featuring quad adjustable shocks with up to 3" travel	BRAKE SYSTEM	6.25" dual rear hydraulic drum with hand operated parking brake
TIRES	25 x 8 - 12 (front) 25 x 10 - 12 (rear)	DIMENSIONS	95" L x 50" W x 77" H
WHEEL BASE	73"	TURNING RADIUS	7.5' inside radius
CURB WEIGHT	1,100 lbs.	BED MATERIAL	Structural foam "Poly Bed" with stake pockets
BED DIMENSIONS	35.25" L x 41.5" W x 11" D	GROUND CLEARANCE	11"
*BED CAPACITY	9 cu.ft. / 400 lbs.	TOWING CAPACITY	1,100 lbs.
TOTAL CAPACITY	800 lbs.	WARRANTY	3-year engine / All other 1-year limited
ADDITIONAL FEATURES	3pt lap/shoulder belts for driver and passenger, twin 12V auxiliary outlets for accessories, 12V/18W LED headlights, polyurethane powder paint, 2" rear receiver hitch, dump had bench seating, welded steel		

FEATURES

receiver hitch, dump bed, bench seating, welded steel frame. Fuel gauge located on fuel tank. In-dash,

hour/volt meter standard