

SPECIFICATIONS

POWER VANGUARD EFI 408cc 14hp motor with electronic throttle control.

SPEED Up to 24 mph**

FUEL CONSUMPTION Up to 20 mpg* *

RANGE Up to 100 miles**

STARTING 12V keyed ignition with recoil backup

BATTERY 12V / 360 cca utility class

SPARK PLUG NGK BPR6ES

FUEL CAPACITY 5.0 gal

ALTERNATOR 25 amp

TRANSMISSION CVT automatic

TRANSAXLE Gear drive Schaefer/DANA oil-filled transaxle

DIFFERENTIAL Cable Actuated Rear-Locking

DRIVE Switch engaged on demand, 4 wheel drive

FRONT SUSPENSION Double A-arms, adjustable coilover shock with up to 7" travel

REAR SUSPENSION Independent trailing arm, with radius rod, adjustable camber & tow control, dual-rate coilover shock with up to 8" of travel

BRAKE SYSTEM 4 wheel disk, hydraulic brake

TIRES 25 x 8 - 12 (front) 25 x 10 - 12 (rear)

DIMENSIONS 95" L x 53" W x 76" H

WHEEL BASE 73"

TURNING RADIUS 7.5' inside radius

CURB WEIGHT 1,100 lbs.

BED MATERIAL Structural foam "Poly Bed" with stake pockets

BED DIMENSIONS 35.25" L x 41.5" W x 11" D

GROUND CLEARANCE 11"

***BED CAPACITY** Poly - 9 cu.ft. / Steel - 11 cu.ft. / L-ROSS - 400 lbs. / HD L-ROSS - 600 lbs.

TOWING CAPACITY 1300 lbs.

TOTAL CAPACITY L-ROSS - 900 lbs. / HD L-ROSS - 1,000 lbs.

WARRANTY 3-year engine / All other 1-year limited

ADDITIONAL FEATURES

3pt lap/shoulder belts for driver and passenger, twin 12V auxiliary outlets for accessories, 12V/18W LED headlights, polyurethane powder paint, 2" front, and rear receiver hitch, poly dump bed standard, weather sealed contoured bench seating, welded steel frame. Complete weather-sealed wiring connections. There is a wide selection of additional accessories and three bed options. Fuel gauge located underside of bed. In-dash, hour/volt meter standard.