SPECIFICATIONS

| POWER | 23hp 627cc Commercial-Grade, V-Twin OHV- Technology, EFI Vanguard 4-stroke Gas Engine. Superior balance, low vibration, lower emissions, improved valve life, better fuel economy and higher HP/Weight. | SPEED | Up to 24 mph** |
|------------------------|---|---------------------|---|
| FUEL CONSUMPTION | Up to 28 mpg* * | RANGE | Up to 100 miles** |
| STARTING | 12V keyed ignition with recoil backup | BATTERY | 12V / 360 cca utility class |
| SPARK PLUG | NGK C7HSA | FUEL CAPACITY | 5.0 gal |
| ALTERNATOR | 25 amp | TRANSMISSION | CVT automatic - Geared for high torque output |
| TRANSAXLE | Gear drive Schafer/DANA oil-filled transaxle | DIFFERENTIAL | Cable Actuated Rear-Locking |
| DRIVE | Switch engaged on demand, 4 wheel drive | FRONT SUSPENSION | Double A-arms, adjustable collover shock with up to 8" travel |
| REAR SUSPENSION | Heavy Duty - Independent trailing arm, with radius rod, adjustable camber & tow control, dual-rate coilover shock with up to 8" of travel | BRAKE SYSTEM | 4 wheel disk, hydraulic brake |
| TIRES | 25 x 10 - 12 (front) 25 x 10 - 12 (rear) | DIMENSIONS | 127" L x 59" W x 76" H |
| WHEEL BASE | 73" | TURNING RADIUS | 14' inside radius |
| CURB WEIGHT | 1625 Lbs. | BED MATERIAL | Steel |
| BED DIMENSIONS | 14.25"h x 50.25" w x 70" L (inside bed dimensions) | GROUND CLEARANCE | 11" |
| *BED CAPACITY | 1000 Lbs 21 cubic feet | TOWING CAPACITY | 1750 lbs. |
| TOTAL CAPACITY | 1,400 lbs. | WARRANTY | 3-year engine / All other 1-year bumper to bumper. |
| ADDITIONAL FEATURES | 3pt lap/shoulder DOT certified belts for driver and passenger with driver indicator light, twin 12V auxiliary outlets for accessories, 12V/18W LED headlights, polyurethane powder paint, 2" front and rear receiver hitch, dump bed, bench seating, welded steel frame. Complete weather-sealed wiring connections. A wide selection of additional accessories is available, along with three bed options. Fuel gauge located underside of bed. In- dash, hour/volt meter standard. | VEHICLE PACKAGES | Powersteering // Trail |